
# Thermal Conductivity of Ag-Doped $Cu_2SnS_3$ Thermoelectric Materials

Laser Flash Analysis (LFA) of Thermal Transport Properties

Laser Flash Analysis (LFA) is a widely used method for determining the thermal diffusivity and thermal conductivity of advanced materials. In this application example, Ag-doped $Cu_2SnS_3$ thermoelectric materials were investigated using the Linseis LFA L51 (former LFA 500) to evaluate their thermal transport behavior over a broad temperature range.
The measurement provides valuable information on heat conduction mechanisms and the influence of silver content on thermoelectric performance.

## Measurement Setup

- Instrument: Linseis LFA L51 (former LFA 500)
- Material: Ag-doped $Cu_2SnS_3$ thermoelectric compounds
- Temperature Range: 300 K – 730 K
- Measurement: Thermal conductivity as a function of temperature
- Method: Laser Flash Analysis (LFA)




The LFA measurement reveals the thermal conductivity behavior of the investigated thermoelectric material.
Key observations include:

- Decreasing thermal conductivity with increasing temperature
- Influence of Ag content on heat transport
- Low conductivity values across the temperature range
- Stable thermal transport behavior

The measurement provides valuable information for thermoelectric material development.

## Interpretation

The observed thermal conductivity behavior can be attributed to:

- Increased phonon scattering
- Temperature-dependent heat transport
- Influence of silver doping on the crystal structure

This results in:

- Reduced thermal conductivity at elevated temperatures
- Improved thermoelectric efficiency potential
- Enhanced material optimization opportunities

## Industrial Relevance

LFA measurements are widely used for:

- Thermoelectric material development
- Waste heat recovery systems
- Energy harvesting technologies
- Thermal transport characterization
- Functional material optimization

## Conclusion

The measurement performed with the Linseis LFA L51 demonstrates the suitability of Laser Flash Analysis for characterizing thermoelectric materials. The temperature-dependent thermal conductivity behavior provides valuable information for the development of efficient energy conversion materials and advanced thermoelectric systems.


Source:
Lohani, K., Nautiyal, H., Ataollahi, N., Anselmi-Tamburini, U., Fanciulli, C., Scardi, P. Enhanced Thermoelectric Performance of Nanostructured $Cu_2SnS_3$ (CTS) via Ag Doping. ACS Applied Nano Materials, 2023, 6, 6323–6333.
https://doi.org/10.1021/acsanm.3c00716
Adapted from thermal diffusivity measurements performed using a Linseis LFA L51 (former designation: LFA 500) Laser Flash Analyzer.